



TALLADIUM, INC.
SAFETY DATA SHEET

27360 W. Muirfield Lane, Valencia • California 91355
(661) 295-0900 • (800) 221-6449

Section 1 - Product and Company Identification

Date of SDS: 11/25/1985

Revision Date: 07/11/2016

Product Identification: Tilite Omega Ceramic Alloy

Product Synonym: Nickel Chrome Alloy

Product Class/Use: Cast Dental Alloy

Company Name: Talladium, Incorporated

Company Address: 27360 West Muirfield Lane
Valencia, California 91355
United States of America

General Information Telephone: (661) 295-0900

Emergency Telephone: Not required by regulations.

Section 2 - Composition/Information on Ingredients

<u>Substance</u>	<u>C.A.S</u>	<u>% Range by weight</u>	<u>OSHA</u> PEL (mg/m ³)	<u>ACGIH</u> TLV (mg/m ³)
Ni	7740-02-0	65.00	1.00	1.00
Cr	7440-47-3	17.00	0.10	0.50
Mo	7439-98-7	13.00	10.00	10.00
Co	7440-48-4	< 1.00	0.10	0.05
Al	7429-90-5	2.00	15.00	10.00
Ti	7440-32-6	< 1.00	N/E	N/E
Beryllide	Not Established	< 2.00	0.005	0.002

In compliance with ADA Guidelines and ISO-9000 for Cast Dental Alloys

Section 3 - Hazards Identification, Including Emergency Overview

Inhalation: May cause irritation to the nose, throat, lungs and mucous membranes. Nickel and Chromium dust may cause headache, dizziness, coughing and difficulty of breathing.

Eyes: Particulate metal dust may be dangerous to the eye and surrounding tissue.

Skin: May cause in some sensitive individuals an allergic response. Nickel prolonged exposure may cause dermatitis.

Ingestion: Ingestion of Nickel or Chromium dust or powder may cause gastrointestinal irritation or liver damage.

Section 4 - First Aid Measures

Inhalation: Remove to fresh air. If breathing is difficult, victim should be given oxygen. If unconscious, evaluate need for artificial respiration and obtain immediate medical attention.

Eyes: If contact occurs, flush eyes immediately with ample water. If irritation develops, seek medical attention.

Skin: If contact occurs, wash skin immediately with water. If product is hot, immediately immerse or flush the affected area with large amounts of cold water to dissipate heat. Cover the affected area with gauze and obtain prompt medical attention.

Ingestion: Swallow large quantities of water. Induce vomiting. Never give anything by mouth to unconscious person.



TALLADIUM, INC.
SAFETY DATA SHEET

Section 5 - Fire Fighting Measures

Extinguishing Media: Not combustible
OSHA Flammability Classification: None
Flash Point/ Method: Not determined

Auto-ignition Temperature: Not determined
Explosive Lower Limit(s): Not determined
Explosive Upper Limit(s): Not determined

Section 6 - Accidental Release Measures

Spill Release Procedures: Allow molten material to solidify and scrape up. Collect material and place in disposal container. Follow relevant local, state, provincial and federal laws and regulations. Avoid contamination of ground water and soil.

Section 7 - Handling and Storage

Handling and Storage Precautions: Use with adequate ventilation. Minimize dust generation and accumulation. Avoid breathing vapors from heated material. Store in dry place

Section 8 - Exposure Controls & Personal Protection

Additional Exposure Limit Information:

Particulates not otherwise classified:

	<i>Value</i>	<i>Limit</i>	<i>Ref.</i>
Inhalation particulate	10 mg/m ³	TWA/TLV	OSHA
Respiration particulate	3 mg/m ³	TWA/TLV	OSHA

Particulates not otherwise regulated:

	<i>Value</i>	<i>Limit</i>	<i>Ref.</i>
Total particulate	15 mg/m ³	TWA/PEL	OSHA
Respiration particulate	5 mg/m ³	TWA/PEL	OSHA

Ventilation: If use generates dust or fumes, use ventilation to control airborne exposure and keep below PEL.

Respiratory Protection: In case of exposure to fumes from hot processing, use appropriate NIOSH-approved respiratory protective equipment.

Eye Protection: Wear safety glasses with side shields.

Skin Protection: Gloves may be desirable for specific work situations. Flame retardant apron when melting.

Other Protective Equipment: A safety shower and eye wash fountain should be readily available. It is recommended that a hazard assessment in accordance with the OSHA Personal Protective Equipment (PPE) Standard in 29 C.F.R. §1910.132 be conducted before using this product in order to identify additional PPE requirements.

Section 9 - Physical & Chemical Properties

Boiling Point: Not available
Melting Point: 2200° F
pH: N/A
Vapor Pressure: N/A
Vapor Density: Heavier than air (i.e., >1)

Specific Gravity: 7.7
Evaporation Rate: N/A
Solubility in Water: N/A
Appearance: Solid
Odor: Odorless



TALLADIUM, INC.
SAFETY DATA SHEET

Section 10 - Stability & Reactivity Data

Stability: Stable under normal storage conditions.

Hazardous Polymerization: Will not occur under normal conditions.

Conditions to Avoid: None in applicable use.

Incompatibility with Other Materials: No known incompatibility with other materials

Hazardous Decomposition Products: No known hazardous decomposition products.

Section 11 - Toxicological Information

Toxicological Information: None available

Section 12 - Ecological Information

Ecological Information: Considered chemically inert in the environment.

Section 13 - Disposal Considerations

Waste Disposal Methods: Follow all federal, state, and local regulations.

Section 14 - Transport Information

U.S. DOT Information: Not regulated.

Section 15 - Regulatory Information

Federal Regulatory Information:

OSHA: This product does contain hazardous material as defined in Section 3. Standard 29 CFR 1910.132.

EPA: This product is not defined as hazardous waste per 40 CFR 261.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III

Section 313: This product contains components subject to reporting requirements.

State Regulatory Information:

Canada: This product is listed on the DSL.

California: Proposition 65: This product contains substances known to the State of California to cause cancer.

Section 16 - Other Information

The information and recommendations above are believed to be accurate and represent the best information currently available to us. The person receiving the above material should make their own determination as to the suitability for their use. Talladium makes no warranty expressed or implied with respect to this information and assumes no liability resulting from its use.

Review Date: 07/13/2016



TALLADIUM, INC.
SAFETY DATA SHEET

27360 W. Muirfield Lane, Valencia • California 91355
(661) 295-0900 • (800) 221-6449

Section 1 - Product and Company Identification

Date of SDS: 11/25/1985

Revision Date: 07/11/2016

Product Identification: Tilite Premium Ceramic Alloy

Product Synonym: Nickel Chrome Alloy

Product Class/Use: Cast Dental Alloy

Company Name: Talladium, Incorporated

Company Address: 27360 West Muirfield Lane
Valencia, California 91355
United States of America

General Information Telephone: (661) 295-0900

Emergency Telephone: Not required by regulations.

Section 2 - Composition/Information on Ingredients

<u>Substance</u>	<u>C.A.S</u>	<u>% Range by weight</u>	<u>OSHA</u> PEL (mg/m ³)	<u>ACGIH</u> TLV (mg/m ³)
Ni	7740-02-0	76.00	1.00	1.00
Cr	7440-47-3	13.00	0.10	0.50
Mo	7439-98-7	5.00	10.00	10.00
Co	7440-48-4	< 1.00	0.10	0.05
Al	7429-90-5	2.00	15.00	10.00
Ti	7440-32-6	< 1.00	N/E	N/E
Beryllide	Not Established	< 2.00	0.005	0.002

In compliance with ADA Guidelines and ISO-9000 for Cast Dental Alloys

Section 3 - Hazards Identification, Including Emergency Overview

Inhalation: May cause irritation to the nose, throat, lungs and mucous membranes. Nickel and Chromium dust may cause headache, dizziness, coughing and difficulty of breathing.

Eyes: Particulate metal dust may be dangerous to the eye and surrounding tissue.

Skin: May cause in some sensitive individuals an allergic response. Nickel prolonged exposure may cause dermatitis.

Ingestion: Ingestion of Nickel or Chromium dust or powder may cause gastrointestinal irritation or liver damage.

Section 4 - First Aid Measures

Inhalation: Remove to fresh air. If breathing is difficult, victim should be given oxygen. If unconscious, evaluate need for artificial respiration and obtain immediate medical attention.

Eyes: If contact occurs, flush eyes immediately with ample water. If irritation develops, seek medical attention.

Skin: If contact occurs, wash skin immediately with water. If product is hot, immediately immerse or flush the affected area with large amounts of cold water to dissipate heat. Cover the affected area with gauze and obtain prompt medical attention.

Ingestion: Swallow large quantities of water. Induce vomiting. Never give anything by mouth to unconscious person.



TALLADIUM, INC.
SAFETY DATA SHEET

Section 5 - Fire Fighting Measures

Extinguishing Media: Not combustible
OSHA Flammability Classification: None
Flash Point/ Method: Not determined

Auto-ignition Temperature: Not determined
Explosive Lower Limit(s): Not determined
Explosive Upper Limit(s): Not determined

Section 6 - Accidental Release Measures

Spill Release Procedures: Allow molten material to solidify and scrape up. Collect material and place in disposal container. Follow relevant local, state, provincial and federal laws and regulations. Avoid contamination of ground water and soil.

Section 7 - Handling and Storage

Handling and Storage Precautions: Use with adequate ventilation. Minimize dust generation and accumulation. Avoid breathing vapors from heated material. Store in dry place

Section 8 - Exposure Controls & Personal Protection

Additional Exposure Limit Information:

Particulates not otherwise classified:

	<i>Value</i>	<i>Limit</i>	<i>Ref.</i>
Inhalation particulate	10 mg/m ³	TWA/TLV	OSHA
Respiration particulate	3 mg/m ³	TWA/TLV	OSHA

Particulates not otherwise regulated:

	<i>Value</i>	<i>Limit</i>	<i>Ref.</i>
Total particulate	15 mg/m ³	TWA/PEL	OSHA
Respiration particulate	5 mg/m ³	TWA/PEL	OSHA

Ventilation: If use generates dust or fumes, use ventilation to control airborne exposure and keep below PEL.

Respiratory Protection: In case of exposure to fumes from hot processing, use appropriate NIOSH-approved respiratory protective equipment.

Eye Protection: Wear safety glasses with side shields.

Skin Protection: Gloves may be desirable for specific work situations. Flame retardant apron when melting.

Other Protective Equipment: A safety shower and eye wash fountain should be readily available. It is recommended that a hazard assessment in accordance with the OSHA Personal Protective Equipment (PPE) Standard in 29 C.F.R. §1910.132 be conducted before using this product in order to identify additional PPE requirements.

Section 9 - Physical & Chemical Properties

Boiling Point: Not available
Melting Point: 2200° F
pH: N/A
Vapor Pressure: N/A
Vapor Density: Heavier than air (i.e., >1)

Specific Gravity: 7.7
Evaporation Rate: N/A
Solubility in Water: N/A
Appearance: Solid
Odor: Odorless



TALLADIUM, INC.
SAFETY DATA SHEET

Section 10 - Stability & Reactivity Data

Stability: Stable under normal storage conditions.

Hazardous Polymerization: Will not occur under normal conditions.

Conditions to Avoid: None in applicable use.

Incompatibility with Other Materials: No known incompatibility with other materials

Hazardous Decomposition Products: No known hazardous decomposition products.

Section 11 - Toxicological Information

Toxicological Information: None available

Section 12 - Ecological Information

Ecological Information: Considered chemically inert in the environment.

Section 13 - Disposal Considerations

Waste Disposal Methods: Follow all federal, state, and local regulations.

Section 14 - Transport Information

U.S. DOT Information: Not regulated.

Section 15 - Regulatory Information

Federal Regulatory Information:

OSHA: This product does contain hazardous material as defined in Section 3. Standard 29 CFR 1910.132.

EPA: This product is not defined as hazardous waste per 40 CFR 261.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III

Section 313: This product contains components subject to reporting requirements.

State Regulatory Information:

Canada: This product is listed on the DSL.

California: Proposition 65: This product contains substances known to the State of California to cause cancer.

Section 16 - Other Information

The information and recommendations above are believed to be accurate and represent the best information currently available to us. The person receiving the above material should make their own determination as to the suitability for their use. Talladium makes no warranty expressed or implied with respect to this information and assumes no liability resulting from its use.

Review Date: 07/13/2016



TALLADIUM, INC.
SAFETY DATA SHEET

27360 W. Muirfield Lane, Valencia • California 91355
(661) 295-0900 • (800) 221-6449

Section 1 - Product and Company Identification

Date of SDS: 11/25/1985

Revision Date: 07/11/2016

Product Identification: Tilite Star Ceramic Alloy

Product Synonym: Nickel Chrome Alloy

Product Class/Use: Cast Dental Alloy

Company Name: Talladium, Incorporated

Company Address: 27360 West Muirfield Lane
Valencia, California 91355
United States of America

General Information Telephone: (661) 295-0900

Emergency Telephone: Not required by regulations.

Section 2 - Composition/Information on Ingredients

<u>Substance</u>	<u>C.A.S</u>	<u>% Range by weight</u>	<u>OSHA</u> PEL (mg/m ³)	<u>ACGIH</u> TLV (mg/m ³)
Ni	7740-02-0	75.00	1.00	1.00
Cr	7440-47-3	12.00	0.10	0.50
Mo	7439-98-7	5.00	10.00	10.00
Co	7440-48-4	< 1.00	0.10	0.05
Al	7429-90-5	3.00	15.00	10.00
Ti	7440-32-6	< 1.00	N/E	N/E
Beryllide	Not Established	< 2.00	0.005	0.002

In compliance with ADA Guidelines and ISO-9000 for Cast Dental Alloys

Section 3 - Hazards Identification, Including Emergency Overview

Inhalation: May cause irritation to the nose, throat, lungs and mucous membranes. Nickel and Chromium dust may cause headache, dizziness, coughing and difficulty of breathing.

Eyes: Particulate metal dust may be dangerous to the eye and surrounding tissue.

Skin: May cause in some sensitive individuals an allergic response. Nickel prolonged exposure may cause dermatitis.

Ingestion: Ingestion of Nickel or Chromium dust or powder may cause gastrointestinal irritation or liver damage.

Section 4 - First Aid Measures

Inhalation: Remove to fresh air. If breathing is difficult, victim should be given oxygen. If unconscious, evaluate need for artificial respiration and obtain immediate medical attention.

Eyes: If contact occurs, flush eyes immediately with ample water. If irritation develops, seek medical attention.

Skin: If contact occurs, wash skin immediately with water. If product is hot, immediately immerse or flush the affected area with large amounts of cold water to dissipate heat. Cover the affected area with gauze and obtain prompt medical attention.

Ingestion: Swallow large quantities of water. Induce vomiting. Never give anything by mouth to unconscious person.



TALLADIUM, INC.
SAFETY DATA SHEET

Section 5 - Fire Fighting Measures

Extinguishing Media: Not combustible
OSHA Flammability Classification: None
Flash Point/ Method: Not determined

Auto-ignition Temperature: Not determined
Explosive Lower Limit(s): Not determined
Explosive Upper Limit(s): Not determined

Section 6 - Accidental Release Measures

Spill Release Procedures: Allow molten material to solidify and scrape up. Collect material and place in disposal container. Follow relevant local, state, provincial and federal laws and regulations. Avoid contamination of ground water and soil.

Section 7 - Handling and Storage

Handling and Storage Precautions: Use with adequate ventilation. Minimize dust generation and accumulation. Avoid breathing vapors from heated material. Store in dry place

Section 8 - Exposure Controls & Personal Protection

Additional Exposure Limit Information:

Particulates not otherwise classified:

	<i>Value</i>	<i>Limit</i>	<i>Ref.</i>
Inhalation particulate	10 mg/m ³	TWA/TLV	OSHA
Respiration particulate	3 mg/m ³	TWA/TLV	OSHA

Particulates not otherwise regulated:

	<i>Value</i>	<i>Limit</i>	<i>Ref.</i>
Total particulate	15 mg/m ³	TWA/PEL	OSHA
Respiration particulate	5 mg/m ³	TWA/PEL	OSHA

Ventilation: If use generates dust or fumes, use ventilation to control airborne exposure and keep below PEL.

Respiratory Protection: In case of exposure to fumes from hot processing, use appropriate NIOSH-approved respiratory protective equipment.

Eye Protection: Wear safety glasses with side shields.

Skin Protection: Gloves may be desirable for specific work situations. Flame retardant apron when melting.

Other Protective Equipment: A safety shower and eye wash fountain should be readily available. It is recommended that a hazard assessment in accordance with the OSHA Personal Protective Equipment (PPE) Standard in 29 C.F.R. §1910.132 be conducted before using this product in order to identify additional PPE requirements.

Section 9 - Physical & Chemical Properties

Boiling Point: Not available
Melting Point: 2200° F
pH: N/A
Vapor Pressure: N/A
Vapor Density: Heavier than air (i.e., >1)

Specific Gravity: 7.7
Evaporation Rate: N/A
Solubility in Water: N/A
Appearance: Solid
Odor: Odorless



TALLADIUM, INC.
SAFETY DATA SHEET

Section 10 - Stability & Reactivity Data

Stability: Stable under normal storage conditions.

Hazardous Polymerization: Will not occur under normal conditions.

Conditions to Avoid: None in applicable use.

Incompatibility with Other Materials: No known incompatibility with other materials

Hazardous Decomposition Products: No known hazardous decomposition products.

Section 11 - Toxicological Information

Toxicological Information: None available

Section 12 - Ecological Information

Ecological Information: Considered chemically inert in the environment.

Section 13 - Disposal Considerations

Waste Disposal Methods: Follow all federal, state, and local regulations.

Section 14 - Transport Information

U.S. DOT Information: Not regulated.

Section 15 - Regulatory Information

Federal Regulatory Information:

OSHA: This product does contain hazardous material as defined in Section 3. Standard 29 CFR 1910.132.

EPA: This product is not defined as hazardous waste per 40 CFR 261.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III

Section 313: This product contains components subject to reporting requirements.

State Regulatory Information:

Canada: This product is listed on the DSL.

California: Proposition 65: This product contains substances known to the State of California to cause cancer.

Section 16 - Other Information

The information and recommendations above are believed to be accurate and represent the best information currently available to us. The person receiving the above material should make their own determination as to the suitability for their use. Talladium makes no warranty expressed or implied with respect to this information and assumes no liability resulting from its use.

Review Date: 07/13/2016



TALLADIUM, INC.
SAFETY DATA SHEET

27360 W. Muirfield Lane, Valencia • California 91355
(661) 295-0900 • (800) 221-6449

Section 1 - Product and Company Identification

Date of SDS: 11/25/1985

Revision Date: 07/11/2016

Product Identification: Tilite "V" Ceramic Alloy

Product Synonym: Nickel Chrome Alloy

Product Class/Use: Cast Dental Alloy

Company Name: Talladium, Incorporated

Company Address: 27360 West Muirfield Lane
Valencia, California 91355
United States of America

General Information Telephone: (661) 295-0900

Emergency Telephone: Not required by regulations.

Section 2 - Composition/Information on Ingredients

<u>Substance</u>	<u>C.A.S</u>	<u>% Range by weight</u>	<u>OSHA</u> PEL (mg/m ³)	<u>ACGIH</u> TLV (mg/m ³)
Ni	7740-02-0	72.00	1.00	1.00
Cr	7440-47-3	14.50	0.10	0.50
Mo	7439-98-7	8.00	10.00	10.00
Co	7440-48-4	< 1.00	0.10	0.05
Al	7429-90-5	2.00	15.00	10.00
Ti	7440-32-6	< 1.00	N/E	N/E
Beryllide	Not Established	< 2.00	0.005	0.002

In compliance with ADA Guidelines and ISO-9000 for Cast Dental Alloys

Section 3 - Hazards Identification, Including Emergency Overview

Inhalation: May cause irritation to the nose, throat, lungs and mucous membranes. Nickel and Chromium dust may cause headache, dizziness, coughing and difficulty of breathing.

Eyes: Particulate metal dust may be dangerous to the eye and surrounding tissue.

Skin: May cause in some sensitive individuals an allergic response. Nickel prolonged exposure may cause dermatitis.

Ingestion: Ingestion of Nickel or Chromium dust or powder may cause gastrointestinal irritation or liver damage.

Section 4 - First Aid Measures

Inhalation: Remove to fresh air. If breathing is difficult, victim should be given oxygen. If unconscious, evaluate need for artificial respiration and obtain immediate medical attention.

Eyes: If contact occurs, flush eyes immediately with ample water. If irritation develops, seek medical attention.

Skin: If contact occurs, wash skin immediately with water. If product is hot, immediately immerse or flush the affected area with large amounts of cold water to dissipate heat. Cover the affected area with gauze and obtain prompt medical attention.

Ingestion: Swallow large quantities of water. Induce vomiting. Never give anything by mouth to unconscious person.



TALLADIUM, INC.
SAFETY DATA SHEET

Section 5 - Fire Fighting Measures

Extinguishing Media: Not combustible

OSHA Flammability Classification: None

Flash Point/ Method: Not determined

Auto-ignition Temperature: Not determined

Explosive Lower Limit(s): Not determined

Explosive Upper Limit(s): Not determined

Section 6 - Accidental Release Measures

Spill Release Procedures: Allow molten material to solidify and scrape up. Collect material and place in disposal container. Follow relevant local, state, provincial and federal laws and regulations. Avoid contamination of ground water and soil.

Section 7 - Handling and Storage

Handling and Storage Precautions: Use with adequate ventilation. Minimize dust generation and accumulation. Avoid breathing vapors from heated material. Store in dry place

Section 8 - Exposure Controls & Personal Protection

Additional Exposure Limit Information:

Particulates not otherwise classified:

	<i>Value</i>	<i>Limit</i>	<i>Ref.</i>
Inhalation particulate	10 mg/m ³	TWA/TLV	OSHA
Respiration particulate	3 mg/m ³	TWA/TLV	OSHA

Particulates not otherwise regulated:

	<i>Value</i>	<i>Limit</i>	<i>Ref.</i>
Total particulate	15 mg/m ³	TWA/PEL	OSHA
Respiration particulate	5 mg/m ³	TWA/PEL	OSHA

Ventilation: If use generates dust or fumes, use ventilation to control airborne exposure and keep below PEL.

Respiratory Protection: In case of exposure to fumes from hot processing, use appropriate NIOSH-approved respiratory protective equipment.

Eye Protection: Wear safety glasses with side shields.

Skin Protection: Gloves may be desirable for specific work situations. Flame retardant apron when melting.

Other Protective Equipment: A safety shower and eye wash fountain should be readily available. It is recommended that a hazard assessment in accordance with the OSHA Personal Protective Equipment (PPE) Standard in 29 C.F.R. §1910.132 be conducted before using this product in order to identify additional PPE requirements.

Section 9 - Physical & Chemical Properties

Boiling Point: Not available

Melting Point: 2200° F

pH: N/A

Vapor Pressure: N/A

Vapor Density: Heavier than air (i.e., >1)

Specific Gravity: 7.7

Evaporation Rate: N/A

Solubility in Water: N/A

Appearance: Solid

Odor: Odorless



TALLADIUM, INC.
SAFETY DATA SHEET

Section 10 - Stability & Reactivity Data

Stability: Stable under normal storage conditions.

Hazardous Polymerization: Will not occur under normal conditions.

Conditions to Avoid: None in applicable use.

Incompatibility with Other Materials: No known incompatibility with other materials

Hazardous Decomposition Products: No known hazardous decomposition products.

Section 11 - Toxicological Information

Toxicological Information: None available

Section 12 - Ecological Information

Ecological Information: Considered chemically inert in the environment.

Section 13 - Disposal Considerations

Waste Disposal Methods: Follow all federal, state, and local regulations.

Section 14 - Transport Information

U.S. DOT Information: Not regulated.

Section 15 - Regulatory Information

Federal Regulatory Information:

OSHA: This product does contain hazardous material as defined in Section 3. Standard 29 CFR 1910.132.

EPA: This product is not defined as hazardous waste per 40 CFR 261.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III

Section 313: This product contains components subject to reporting requirements.

State Regulatory Information:

Canada: This product is listed on the DSL.

California: Proposition 65: This product contains substances known to the State of California to cause cancer.

Section 16 - Other Information

The information and recommendations above are believed to be accurate and represent the best information currently available to us. The person receiving the above material should make their own determination as to the suitability for their use. Talladium makes no warranty expressed or implied with respect to this information and assumes no liability resulting from its use.

Review Date: 07/13/2016